

GBJ15005 THRU GBJ1510

Glass Passivated Bridge Rectifiers

Reverse Voltage - 50 to 1000 Volts
Forward Current - 15 Amperes

Features

- Glass passivated chip
- Low forward voltage drop
- Ideal for printed circuit board
- High surge current capability


Mechanical Data

- Polarity: Symbol marked on body
- Mounting position: Any


Applications

- General purpose use in AC/DC bridge full wave rectification, for SMPS, lighting ballaster, adapter, etc.

GBJ



RoHS
COMPLIANT



Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

Characteristics	Symbol	GBJ	GBJ	GBJ	GBJ	GBJ	GBJ	GBJ	Unit
		15005	1501	1502	1504	1506	1508	1510	
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward (with heatsink Note 2) Rectified Current @ $T_c=100^\circ\text{C}$ (without heatsink)	$I_{(AV)}$	15.0							A
Peak Forward Surge Current, 8.3mS Single Half Sine-Wave, Superimposed on Rated Load (JEDEC Method)	I_{FSM}	3.7							A
I^2t Rating for Fusing ($t < 8.3\text{mS}$)	I^2t	240							A^2s
Peak Forward Voltage per Diode at 7.5A DC	V_F	1.0							V
Maximum DC Reverse Current at Rated @ $T_J=25^\circ\text{C}$	I_R	5.0							μA
DC Blocking Voltage per Diode @ $T_J=125^\circ\text{C}$		500							
Typical Junction Capacitance per Diode (Note1)	C_J	60							pF
Typical Thermal Resistance to Ambient (Note2)	$R_{\theta JA}$	4.5							$^\circ\text{C}/\text{W}$
Typical Thermal Resistance to case (Note2)	$R_{\theta JC}$	0.8							
Typical Thermal Resistance to lead (Note2)	$R_{\theta JL}$	1.5							
Operating Junction Temperature Range	T_J	-55 to +150							$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-55 to +150							$^\circ\text{C}$

- Notes: 1. Measured at 1.0 MHz and applied reverse voltage of 4.0V DC.
2. Device mounted on 300mm*300mm*1.6mm Cu plate heatsink.
3. The typical data above is for reference only

GBJ15*-U/B-00/99-00/01
Rev. 9, 22-Apr-2019

Rating and Characteristic Curves

GBJ15005 THRU GBJ1510

Fig. 1 - Forward Current Derating Curve




Fig. 2 - Maximum Non-Repetitive Surge Current




Fig. 3 - Typical Reverse Characteristics




Fig. 4 - Typical Forward Characteristics





Fig. 5 - Typical Junction Capacitance



The curve above is for reference only.

